



Securit 802

Eight Zone Control Panel



Easy to use residential/
light commercial
alarm control panel

Features

- **Sleek Design**
Complete with an integral keypad, the Securit 802 is designed so that its handsome aesthetics will blend into most environments and be easy on the eye.
- **Easy to Operate**
The backlit keypad is simple to use and provides a positive tactile and audio response giving confidence in operation. Should additional arming points be required, compact remote keypads can be added to the system.

UK Security Panels

Features

Eight Zones (Alarm)

6 Programmable for: Alarm, Entry/Exit, Access (walk through), Personal Attack, Part Set Entry, Part Set Isolation.

1 Programmable for: Entry, Alarm, Fire, Keypress.

1 Fixed: Entry/Exit.

Door Sense Setting

Allows easy setting of the system without having to wait for the exit timer to Run out.

Home Set Facility

Gives flexibility by automatically isolating pre-programmed zones, allowing the system to be armed while the User remains inside.

Manual Isolation

The system can be tailored for any situation that arises by isolating individual zones which have not been programmed for Home or Part Set Isolation.

Remote P.A. Option

The Remote keypads can be programmed to give a Personal Attack Feature, using the * and # Keys.

Extension Speaker Output

For greater enhanced sounds, up to two 16 Ohm extension speakers can be fitted.

Chime Function

Enabling this feature allows Monitoring of chosen zones while the panel is disarmed.

Two User Codes

Main User code plus second code for children or cleaner etc.

Event Memory

Allows checking of past events.

Specifications

Securit 802 Control Panel

Dimensions

Height : 254mm

Width : 195mm

Depth : 60mm

Material : white, moulded polycarbonate

Weight : 1.21 kg

Mains Supply Voltage

230 V AC Nominal.

PSU Output Voltage

13.6 V Nominal.

Maximum Output Current

1 A (total).

Panel Quiescent

40 mA.

Normal operating temperature

0°C to 40°C

Humidity

10 to 90% R.H. non-condensing.

Keypad

Keypads

Dimensions:

Height : 70mm

Width : 120mm

Depth : 25mm

Supply Voltage

12 V.

Quiescent Current

20 mA.

Active

45 mA.

Maximum number allowed

Six.

Approvals

CE Designed to comply with BS4737 Part I, and BSEN50131-1 (Grades 1&2).

Ordering Part Number

ST 802.

For further information, please contact:

